



All dimensions shown are in millimetres

All stainless steel construction: **30x30x1.5mm square headers**  
**dia 18mm x 1.5mm round tubes**

Connections: **1.2m long flying lead (3 core)**

Immersion heater rating: **IPX4 or better**

Manufactured in Russia for Bisque

Model	Output Watts	Weight kg	Height ± 2mm	Length ± 2mm	Fixing Centres ± 5mm
OLAE-90-30/F	100	6	900	300	270
OLAE-90-50/F	100	7	900	480	450
OLAE-120-50/F	150	8	1200	480	450
OLAE-120-65/F	200	11	1200	630	600
OLAE-155-50/F	250	12	1575	480	450

## Tools & Material Required

Screwdriver - flathead  
 Pliers  
 Electric drill  
 Masonry drill bit  
 Spirit level  
 Stepladder (for taller radiators)

Key	Component	Qty
A	Wall Plug	4
B	Bracket	4
C	Screw - Hex Head, 6mm dia x 60mm	4
D	Washer	4
E	Grub Screw	4
F	Allen Key	1

## Assembly Instructions

Accurately mark out bracket holes on wall using spirit level.

Drill four holes to a minimum depth of 65mm & insert wall plugs (A).

Screw brackets (B) into wall plugs (A) with 6mm diameter x 70mm screws (C) & washers (D).

Offer radiator up to wall and slide square posts on the rear of the radiator into brackets (B).

Secure radiator in position by tightening Allen headed screw (E) with Allen key (F).

Electric radiators should be fitted only by a qualified electrician and must be earthed and connected to a cable outlet in the bathroom in accordance with I.E.E. wiring regulations. The electrical connection should be made to a '5 amp fused fixed spur' located outside the bathroom.

*Note: for maintenance purposes, cable outlets must remain accessible and cables must not be buried directly into walls.*

